


Thermal Link P-5A-F Series

5A Series

Key Features

- Ceramic case
- Non-resettable
- High accuracy of function temperature
- RoHS & REACH compliant

Dimensions



Specification

Model	T _f (°C)	Fusing Temp. (°C)	T _h (°C)	T _m (°C)	I _r (A)	U _r (V)	UL [®] UL recognized	cUL [®] cUL recognized	VDE	PSE	CCC	KTL	RoHS REACH
P0-5A-F	84	82±2	65	200	5	AC 250	●	●	●	●	●	●	●
P1-5A-F	102	98±2	80	200	5	AC 250	●	●	●	●	●	●	●
P2-5A-F	115	112±3	95	200	5	AC 250	●	●	●	●	●	●	●
P3-5A-F	125	120±3	105	200	5	AC 250	●	●	●	●	●	●	●
P4-5A-F	130	126±2	107	200	5	AC 250	●	●	●	●	●	●	●
P5-5A-F	135	131±3	115	200	5	AC 250	●	●	●	●	●	●	●
P9-5A-F	138	135±2	115	200	5	AC 250	●	●	●	●	●	●	●
P12-5A-F	145	140±2	126	200	5	AC 250			●	●	●	●	●
P7-5A-F	150	145±3	128	200	5	AC 250	●	●	●	●	●	●	●